

P037183/WO/1

- 13 -

DaimlerChrysler AG

Patent Claims

5 1. A storage compartment for a vehicle, preferably
for passenger vehicles,
having a deposit compartment and a pivotably mounted
storage compartment cover for closing the deposit
compartment, the storage compartment cover having an
10 axis of rotation on two opposite longitudinal edges and
being able to be opened in two directions and pivoting
either about one axis of rotation or the other axis of
rotation,
characterized
15 in that, in the closed position of the storage
compartment cover (2), the two axes of rotation (21,
22) are locked and, after release of the lock of one
axis of rotation (21 or 22), a driving device (3)
automatically pivots the storage compartment cover (2)
20 about the other axis of rotation (22 or 21) in the
opening direction.

2. The storage compartment as claimed in claim 1,
characterized
25 in that a retaining device (4) which is designed for
locking both axes of rotation (21, 22) is arranged on a
side wall (13) of the deposit compartment (11).

3. The storage compartment as claimed in claim 2,
30 characterized
in that a release button (41) is arranged in the region
of the side wall (13) of the deposit compartment (11),
is connected to the retaining device (4) and interacts
therewith to release one axis of rotation (21 or 22).

35 4. The storage compartment as claimed in claim 2 or
3,
characterized

REPLACED BY
ART 34 AMDT

P037183/WO/1

- 14 -

in that the storage compartment cover (2) has spindle stubs (23, 24) which are arranged in the region of the axes of rotation (21, 22) and run along the two axes of rotation (21, 22), and provision is preferably made for one spindle stub (24) to extend on one side of the storage compartment cover (2) beyond the latter and to engage in the retaining device (4) to lock and/or support the storage compartment cover (2).

5. The storage compartment as claimed in one of claims 1 to 4, characterized

in that the driving device (3) has an energy store (32, 33) which is designed in such a manner that it is charged during the manual closing of the storage compartment cover (2) and is discharged during the automatically driven opening of the storage compartment cover (2).

6. The storage compartment as claimed in one of claims 1 to 5, characterized

in that each axis of rotation (21, 22) is connected to an energy store (32, 33), preferably a spring with a damping device.

7. The storage compartment as claimed in one of claims 1 to 6, characterized

in that one axis of rotation (21 or 22) has two spindle stubs (23, 24) which can be displaced linearly on the storage compartment cover (2) along the axis of rotation (21 or 22), each spindle stub (23 or 24) having, at the end facing the other spindle stub (24 or 23), a rack (25) which meshes via a toothed wheel (26) with the rack (25) of the other spindle stub (23 or 24) in such a manner that the spindle stubs (23, 24) move in opposed directions.

REPLACED BY
ART 34 AMDT

P037183/WO/1

- 15 -

8. The storage compartment as claimed in one of claims 1 to 7, characterized

5 in that an axis of rotation (21, 22) has a blocking device (42) which is designed in such a manner that it blocks a release of the axis of rotation (21, 22) when the storage compartment cover (2) is open.

10 9. The storage compartment as claimed in one of claims 6 to 8, characterized

in that the energy store (32) of the first axis of rotation (21) is arranged in the storage compartment cover (2) in the region of the axis of rotation (21) and the energy store (33) of the second axis of rotation (22) is arranged in the region of a side wall (13) of the deposit compartment (11).

20 10. The storage compartment as claimed in one of claims 6 to 9, characterized

in that the retaining device (4) has a bar (28) which connects the two axes of rotation (21, 22), is connected to the energy store (33) of the second axis of rotation (22) and, after the first axis of rotation (21) is released, pivots the storage compartment cover (2) about the second axis of rotation (22) in the opening direction.

30 11. The storage compartment as claimed in claim 10, characterized

in that the bar (27, 28) is designed in such a manner that, when the second axis of rotation (22) is released, the bar (28) is arranged in a fixed position on the side wall (13) and forms the rotary bearing of the first axis of rotation (21), and in that, when the first axis of rotation (21) is released, the bar (27,

REPLACED BY
ART 34 AMDT

P037183/WO/1

- 16 -

28) pivots together with the storage compartment cover (2).

12. The storage compartment as claimed in one of
5 claims 1 to 6,
characterized
in that the energy store (32) of the first axis of
rotation (21) and the energy store (33) of the second
axis of rotation (22) are accommodated in the storage
10 compartment cover (2) and both energy stores (32, 33)
are preferably arranged in the region of the axes of
rotation (21, 22).

13. The storage compartment as claimed in claim 12,
15 characterized
in that the energy store (32) of the first axis of
rotation (21) is connected to the energy store (33) of
the second axis of rotation (22), preferably by means
of a rack (35) and/or a flexible shaft (36), so that
20 the two energy stores (32, 33) interact in each case to
pivot the storage compartment cover (2) about an axis
of rotation (21, 22).

14. The storage compartment as claimed in claim 12 or
25 13,
characterized
in that the energy store (32, 33) is designed for
storing equal amounts of energy in the energy store
(32) of the first axis of rotation (21) and in the
30 energy store (33) of the second axis of rotation (22)
by the rack and/or the flexible shaft (36) transferring
energy between the energy stores (32, 33) when the
storage compartment cover (2) is pivoted.

15. The storage compartment as claimed in one of
35 claims 12 to 14,
characterized

REPLACED BY
ART 34 AMDT

P037183/WO/1

- 17 -

in that the spindle stubs (24), at their end reaching beyond the storage compartment cover (2), have a cam (37) which is preferably elliptical or polygonal in shape and which, when the retaining device (4) is
5 locked, engages in the latter in such a manner that the particular spindle stub (24) is mounted in a rotationally fixed manner in the retaining device (4).

REPLACED BY
ART 34 AMDT